

# APPLICATION FOR UNITED STATES PATENT

## EXCISIONAL BIOPSY DEVICES AND METHODS

5

10  
INVENTOR      Name:            Roberta LEE, M.D.  
                    Address:        1017 El Camino Real, No. 436,  
   Redwood City CA 94063  
                    Citizenship:    USA

15  
INVENTOR      Name:            James W. VETTER, MD  
                    Address:        117 Solana Road  
   Portola Valley CA 94028  
                    Citizenship:    USA

20  
INVENTOR      Name:            Ary S. CHERNOMORSKY  
                    Address:        380 Vallejo Drive, Suite 304  
   Millbrae, CA 94030  
                    Citizenship:    USA

25  
ASSIGNEE      RUBICOR MEDICAL, INC.  
                    2900 Whipple Avenue, Suite 230  
                    Redwood City, CA 94063

Young Law Firm, P.C.  
4370 Alpine Road, Suite 106  
Portola Valley, CA 94028  
Tel: (650) 851-7210  
Fax: (650) 851-7232

## BACKGROUND OF THE INVENTION

### 1. Cross Reference to Related Applications

The present application is a continuation-in-part of US patent application serial number 09/417,520, which is a divisional patent application of US patent application serial  
5 number 09/146,743, now patent number 6,022,362.

### 2. Field of the Invention

The present invention pertains to the field of soft tissue excisional biopsy devices and methods. In particular, the present invention relates to the field of devices and methods for excising suspicious lesions from soft tissue, such as breast tissue.

### 10 3. Description of the Related Art

Breast cancer is a major threat and concern to women. Early detection and treatment of suspicious or cancerous lesions in the breast has been shown to improve long-term survival of the patient. The trend is, therefore, to encourage women not only to perform monthly self-breast examination and obtain a yearly breast examination by a qualified  
15 physician, but also to undergo annual screening mammography commencing at age 40. Mammography is the only screening modality available today that can detect small, nonpalpable lesions. These nonpalpable lesions may appear as opaque densities relative to normal breast parenchyma and fat or as clusters of microcalcifications.

The conventional method for diagnosing, localizing and excising nonpalpable lesions  
20 detected by mammography generally involves a time-consuming, multi-step process. First, the patient goes to the radiology department where the radiologist finds and localizes the lesion either using mammography or ultrasound guidance. Once localized, a radio-opaque

wire is inserted into the breast. The distal end of the wire may include a small hook or loop. Ideally, this is placed adjacent to the suspicious area to be biopsied. The patient is then transported to the operating room. Under general or local anesthesia, the surgeon performs a procedure called a needle-localized breast biopsy. In the needle-localized breast biopsy, the surgeon, guided by the wire previously placed in the patient's breast, excises a mass of tissue around the distal end of the wire. The specimen is sent to the radiology department where a specimen radiograph is taken to confirm that the suspicious lesion is contained within the excised specimen. Meanwhile, the surgeon, patient, anesthesiologist and operating room staff, wait in the operating room for confirmation of that fact from the radiologist before the operation is completed. The suspicious lesion should ideally be excised in toto with a small margin or rim of normal breast tissue on all sides. Obtaining good margins of normal tissue is extremely dependent upon the skill and experience of the surgeon, and often an excessively large amount of normal breast tissue is removed to ensure that the lesion is located within the specimen. This increases the risk of post-operative complications, including bleeding and permanent breast deformity. As 80% of breast biopsies today are benign, many women unnecessarily suffer from permanent scarring and deformity from such benign breast biopsies.

More recently, less invasive techniques have been developed to sample or biopsy the suspicious lesions to obtain a histological diagnosis. The simplest of the newer techniques is to attempt visualization of the lesion by external ultrasound. If seen by external ultrasound, the lesion can be biopsied while being continuously visualized. This technique allows the physician to see the biopsy needle as it actually enters the lesion, thus ensuring that the

correct area is sampled. Current sampling systems for use with external ultrasound guidance include a fine needle aspirate, core needle biopsy or vacuum-assisted biopsy devices.

Another conventional technique localizes the suspicious lesion using stereotactic digital mammography. The patient is placed prone on a special table that includes a hole to allow the designated breast to dangle therethrough. The breast is compressed between two mammography plates, which stabilizes the breast to be biopsied and allows the digital mammograms to be taken. At least two images are taken 30 degrees apart to obtain stereotactic views. The x, y and z coordinates targeting the lesion are calculated by a computer. The physician then aligns a special mechanical stage mounted under the table that places the biopsy device into the breast to obtain the sample or samples. There are believed to be three methods available to biopsy lesions using a stereotactic table: (1) fine needle aspiration, (2) core needle biopsy and (3) vacuum-assisted core needle biopsy.

Fine needle aspiration uses a small gauge needle, usually 20 to 25 gauge, to aspirate a small sample of cells from the lesion or suspicious area. The sample is smeared onto slides that are stained and examined by a cytopathologist. In this technique, individual cells in the smears are examined, and tissue architecture or histology is generally not preserved. Fine needle aspiration is also very dependent upon the skill and experience of the operator and can result in a high non-diagnostic rate (up to about 83%), due to inadequate sample collection or preparation.

Core needle biopsy uses a larger size needle, usually 14 gauge to sample the lesion. Tissue architecture and histology are preserved with this method. A side-cutting device, consisting of an inner trough with an outer cutting cannula is attached to a spring-loaded device for a rapid semi-automated firing action. After the lesion is localized, local

anaesthetic is instilled and a small incision is made in the skin with a scalpel. The device enters the breast and the needle tip is guided into the breast up to the targeted lesion. The device is fired. First, the inner cannula containing the trough rapidly penetrates the lesion. Immediately following this, the outer cutting cannula rapidly advances over the inner cannula cutting a sample of tissue off in the trough. The whole device is then removed and the sample retrieved. Multiple penetrations of the core needle through the breast and into the lesion are required to obtain an adequate sampling of the lesion. Over 10 samples have been recommended by some.

The vacuum-assisted breast biopsy system is a larger semi-automated side-cutting device. It is usually 11 gauge in diameter and is more sophisticated than the core needle biopsy device. Multiple large samples can be obtained from the lesion without having to reinsert the needle each time. A vacuum is added to suck the tissue into the trough. The rapid firing action of the spring-loaded core needle device is replaced with an oscillating outer cannula that cuts the breast tissue off in the trough. The physician controls the speed at which the outer cannula advances over the trough and can rotate the alignment of the trough in a clockwise fashion to obtain multiple samples.

If a fine needle aspirate, needle core biopsy or vacuum-assisted biopsy shows malignancy or a specific benign diagnosis of atypical hyperplasia, then the patient needs to undergo another procedure, the traditional needle-localized breast biopsy, to fully excise the area with an adequate margin of normal breast tissue. Sometimes the vacuum-assisted device removes the whole targeted lesion. If this occurs, a small titanium clip should be placed in the biopsy field. This clip marks the area if a needle-localized breast biopsy is subsequently required for the previously mentioned reasons.

Another method of biopsying the suspicious lesion utilizes a large end-cutting core device measuring 0.5 cm to 2.0 cm in diameter. This also uses the stereotactic table for stabilization and localization. After the lesion coordinates are calculated and local anesthesia instilled, an incision large enough to permit entry of the bore is made at the entry site with a scalpel. The breast tissue is cored down to and past the lesion. Once the specimen is retrieved, the patient is turned onto her back and the surgeon cauterizes bleeding vessels under direct vision. The incision, measuring 0.5 to larger than 2.0 cm is sutured closed.

The stereotactic table requires awkward positioning of the patient and may be extremely uncomfortable. The woman must lie prone during the entire procedure, which may be impossible for some patients. In addition, the lesion to be biopsied must be in the center working area of the mammography plates. This may be extremely difficult and uncomfortable for the patient if the lesion is very posterior near the chest wall or high towards the axilla.

The woman is subjected to increased radiation exposure as multiple radiographs are required throughout the course of the procedure to: (1) confirm that the lesion is within the working area of the mammography plates, (2) obtain the stereotactic coordinates (at least two views), (3) verify the positioning of the biopsy needle prior to obtaining tissue, and (4) verify that the lesion was indeed sampled. If any difficulty is encountered during the procedure, additional radiographic exposures are required to verify correction of the problem.

Using the core needle biopsy or vacuum-assisted device, bleeding is controlled only by manual pressure. Bleeding is generally not an issue with fine needle aspiration, but is a legitimate complication of the former two methods. Ecchymoses, breast edema and hematomas can occur. This causes increased post-procedural pain and delays healing.

Rarely, the patient may require an emergency operation to control and evacuate a tense hematoma.

Another major concern is the possibility of tumor dissemination. The core needle biopsy and vacuum-assisted devices both cut into the tumor and carve out multiple samples for examination. While cutting into the tumor, cancerous cells may be dislodged. Cutting across blood vessels at the same time may allow the freed cancerous cells access to the blood stream, thus possibly seeding the tumor beyond its original locus. The long-term consequences of tumor seeding with the risk of bloodborne metastases are unknown at this time, as the techniques are relatively new. However, documented instances of cancerous cells seeding locally into needle tracks exist. There are numerous reports of metastases growing in needle tracks from previous biopsies of a cancerous mass. Most of these are from lung or liver cancers. However, at least one case of mucinous carcinoma of the breast growing in a needle track has been reported. The long-term consequences of neoplasm seeding into needle tracks are currently unknown, again because the techniques are relatively new. Some recommend excision of the entire needle track, including the skin entry site, during the definitive surgical procedure for a diagnosed cancer, whether it is a lumpectomy or a mastectomy. Others assume that with a lumpectomy, the post-operative radiation therapy will destroy any displaced cancer cells in the needle track. With the trend towards treating very small cancers only by excision and without a post-excision course of radiation therapy, the risk of cancer cells metastasizing and growing in needle tracks is very real.

The large core cutting device (0.5 cm to 2.0 cm) generally eliminates the risk of needle track seeding as it is designed to excise the lesion intact. A stereotactic table is required with the same inherent awkwardness for the patient, as discussed above. Bleeding is

controlled, albeit manually, requiring that the patient wait until the end of the procedure to be turned over. Compression is used to stabilize the breast and localize the lesions. The breast, however, may be torqued and distorted between the compression plates such that when the plates are removed after the biopsy, the large core track left behind may not be straight, but actually tortuous. This can result in permanent breast deformity.

The location of the insertion site into the breast is dictated by the positioning of the breast in the machine and not by the physician. The entry site is usually away from the nipple-areolar complex and is usually located on the more exposed areas of the breast. For the fine needle aspirate, core biopsy and vacuum-assisted devices, the incision is usually very small and the scar almost unappreciable. However, in the case of the large core biopsy device (0.5 to 2.0 cm), a large incision is needed. Such a large incision often results in a non-aesthetically placed scar.

The newer conventional minimally invasive breast biopsy devices have improved in some ways the ability to diagnose mammographically detected nonpalpable lesions. These devices give the patient a choice as to how she wants the diagnosis to be made. Moreover, these devices are substantially less expensive than the older traditional needle-localized breast biopsy. They are not, however, the final solution. Due to the above-discussed problems and risks associated with compression, needle-track seeding, blood borne metastases, bleeding, radiation exposure and awkwardness of the stereotactic table, more refined devices and methods are needed to resolve these issues. Also, the conventional biopsy devices do not consider margins in their excisions and if cancer is diagnosed, the patient must undergo a needle-localized breast lumpectomy to ensure that adequate margins are removed around the cancer. Devices and methods, therefore, must address the problem of



obtaining adequate margins so that a second procedure is not required. Margins, moreover, cannot be assessed while the breast is being compressed.

## SUMMARY OF THE INVENTION

It is, therefore, an object of the present invention to provide devices and methods to efficiently and safely excise suspicious lesions from the breast. It is also an object of the present invention to provide devices and methods that remove the entire lesion intact with the minimum amount of normal tissue surrounding the lesion needed to provide adequate margins. It is a further object of the present invention to provide devices and methods that provide hemostasis in the breast to minimize complications of ecchymosis, hematoma formation, and breast edema. It is another object of the present invention to provide methods and devices to provide intra-tissue ultrasonic guidance to provide real time, in situ monitoring of the procedure. A still further object is to provide devices and methods that allow the physician to minimize the size of the incision through which the procedure is performed and to leave an aesthetically acceptable scar on the breast.

In accordance with the above-described objects and those that will be mentioned and will become apparent below, an embodiment of an excisional biopsy system according to the present invention comprises a tubular member including a proximal end and a distal end, the tubular member defining a first window near the distal end, and a first removable probe that includes a proximal portion including cutting tool extending means, a distal portion and a cutting tool near the distal portion, the first removable probe being configured to fit at least partially within the tubular member to enable the cutting tool to selectively bow out of and to retract within the first window when the cutting tool extending means are activated.

The first removable probe may further include a window slide and the proximal end may further include a window slide extending means, the window slide being configured to selectively cover a portion of the first window when the window slide extending means are activated. The cutting tool may include one of a thin ribbon sharpened on a leading edge thereof and a wire. The cutting tool may include an RF cutting tool and the first removable probe may be adapted to be connected to an RF power source. The cutting tool may include a monopolar or a bipolar RF cutting tool. The tubular member may include a first internal guide that is configured to enable the first removable probe to slide within the tubular member. The first removable probe may include a second internal guide, the second internal guide enabling the cutting tool to slide within the first removable probe when the cutting tool extending means are activated. The first removable probe may include a third internal guide, the third internal guide enabling the window slide to slide within the first removable probe when the window slide extending means are activated. The biopsy system may further include a second removable probe comprising a proximal section including a tissue collection device extending means and a distal section including a tissue collection device, the second removable probe being configured to fit at least partially within the tubular member to enable the tissue collection device to extend out of and to retract within the first window when the tissue collection device extending means are activated. Alternatively, the tubular member may define a second window near the distal end thereof, and the biopsy system may further include a second removable probe comprising a proximal section including a tissue collection device extending means and a distal section including a tissue collection device, the second removable probe being configured to fit at least partially within the tubular member to enable

the tissue collection device to selectively extend out of and to retract within the second window when the tissue collection device extending means are activated.

The tissue collection device may include a thin ribbon or a wire, as well as a thin flexible sheet of material attached to the thin ribbon or wire, the thin flexible sheet at least partially encapsulating a tissue specimen as the thin ribbon or wire is extended and the tubular member rotated. The thin flexible sheet of material may include a bag attached to the ribbon or wire so as to open and close when the ribbon or wire is extended and retracted, respectively. The tissue collection device may include a thin ribbon or a wire, and a thin flexible sheet of material may be attached to the thin ribbon or wire, the thin flexible sheet at least partially encapsulating a tissue specimen as the thin ribbon or wire is extended and the tubular member rotated. The thin flexible sheet of material may include a bag attached to the thin ribbon or wire so as to open and close when the thin ribbon or wire is extended and retracted, respectively. The tubular member may include a first internal guide that is configured to enable one of the first and the second removable probe to slide within the tubular member until the cutting tool and/or the tissue collection device faces out of the first window. Similarly, the tubular member may include a second internal guide that is configured to enable the second removable probe to slide within the tubular member until the tissue collection device faces out of the second window. The distal portion of the first removable probe may further include a tissue collection device near a trailing edge of the cutting tool, the tissue collection device being configured to selectively extend out of and retract into the first window. The proximal portion of the first removable probe may include a tissue collection device extending means, the tissue collection device extending means being adapted to enable the tissue collection device to extend out of and to retract within the

first window independently of the cutting tool. The tissue collection device may be coupled to the cutting tool and the cutting tool extending means may also be configured to selectively extend the tissue collection device out of the first window and retract the tissue collection device into the first window as the cutting tool is extended and retracted, respectively. The first removable probe may include an insulator between the tissue collection device and the cutting tool. The insulator may include an air gap and/or an insulating material attached to and separating the cutting tool from the tissue collection device. The first removable probe may define one or more internal lumens that terminate near the distal portion as an opening formed in a surface of the first removable probe, the opening being adapted to deliver a pharmaceutical agent and/or to provide suction.

A third removable probe may be provided, the third removable probe being configured to fit at least partially within the tubular member and including an imaging device mounted therein. The imaging device may include an ultrasound sensor, such as a linear array of ultrasound transducers, for example. The ultrasound sensor may be disposed near a distal tip of the third removable probe and away from the cutting tool, so that the ultrasound sensor sweeps a plane ahead of the cutting tool as the tubular member rotates. The ultrasound sensor may be tuned within the range from about 7.5 MHz to about 20 MHz. The ultrasound sensor may be disposed within the tubular member at an angle  $\alpha$  relative to the cutting tool, the angle  $\alpha$  being no smaller than that necessary to effectively control the operation of the cutting tool in response to information gathered from the ultrasound transducer as the tubular member rotates. For example, the angle  $\alpha$  may be less than about 90 degrees.

The tubular member, first removable probe, the second removable probe and/or the third removable may be configured for a single use and may be disposable.

The present invention is also a soft tissue treatment method, comprising the steps of inserting a generally tubular member into the soft tissue, the tubular member defining a first window in a surface thereof, the tubular member being configured to accept a removable probe inserted therein; inserting a first removable probe into the tubular member, the first removable probe including a cutting tool that is adapted to face out of the first window; selectively activating the cutting tool to cut a tissue specimen while rotating the tubular member within the tissue; removing the first removable probe from the tubular member while the tubular member stays in place; inserting a second removable probe into the tubular member, the second removable probe including a tissue collection device that is adapted to face out of the first window, and selectively activating the tissue collection device to encapsulate the tissue specimen rotating the tubular member.

The first removable probe may be inserted into the tubular member before the tubular member is inserted into the soft tissue. The method may further include the steps of inserting a third removable probe into the tubular member, the third removable probe including an imaging device therein that is configured to face out of the first window, and rotating the tubular member while activating the imaging device to image the soft tissue at least one of before and after the tissue collection device is activated. The tubular member may define a second window in the surface thereof and the method may further include the steps of inserting a third removable probe into the tubular member, the third removable probe including an imaging device therein that is configured to face out of the second window, and

rotating the tubular member while activating the imaging device to image the soft tissue at least one of before, during and after the tissue collection device is activated.

Steps may be carried out to display information received from the imaging device on a display device and to vary the operation of the cutting tool and/or the tissue collection device during the first and/or second activating steps based upon the displayed information from the imaging device. The cutting tool may include an electrosurgical blade and the method may further include the step of varying a power applied to the electrosurgical blade based upon information received from the imaging device or feedback to the RF generator. A step of stabilizing the soft tissue in an uncompressed state prior to the first inserting step may also be carried out.

The tubular member and/or the first removable probe may define an internal lumen and a plurality of through holes in fluid communication with the internal lumen, and the method may further comprise one or more of the following steps: delivering a pharmaceutical agent to the tissue via the plurality of through holes, and suctioning smoke and/or fluids from the soft tissue via the plurality of through holes.

The present invention may also be viewed as a soft tissue treatment method, comprising the steps of inserting a generally tubular member into the soft tissue, the tubular member defining a first window in a surface thereof, the tubular member being configured to accept a removable probe inserted therein; inserting a first removable probe into the tubular member, the first removable probe including a cutting tool and a tissue collection device that are adapted to face out of the first window; selectively activating the cutting tool to cut a tissue specimen while rotating the tubular member within the soft tissue, and selectively

activating the tissue collection device to encapsulate the tissue specimen while rotating the tubular member.

The first removable probe may be inserted into the tubular member before the tubular member is inserted into the soft tissue. The tubular member may define a second window in the surface thereof and the method may further include the steps of inserting a second removable probe into the tubular member, the second removable probe including an imaging device therein that is configured to face out of the second window, and rotating the tubular member while activating the imaging device to image the soft tissue at least one of before, during and after at least one of the cutting tool and the tissue collection device are activated. The method may also include the steps of displaying information received from the imaging device on a display device; and varying an operation of at least one of the cutting tool and the tissue collection device during at least one the first and second rotating steps based upon the displayed information from the imaging device.

The first and second activating steps may be carried out simultaneously and the cutting tool and the tissue collection device may be coupled to one another. Alternatively, the first and second activating steps may be carried out simultaneously or consecutively and the cutting tool and the tissue collection device may be activated independently of one another.

According to another embodiment thereof, the present invention is also an excisional biopsy system for soft tissue, comprising a tubular member defining a first, a second and a third window near a distal tip thereof; a first removable probe comprising a proximal portion that includes cutting tool extending means, a distal portion and a cutting tool near the distal portion, the first removable probe being configured to fit at least partially within the tubular

member to enable the cutting tool to selectively bow out of and to retract within the first window when the cutting tool extending means are activated; a second removable probe comprising a proximal section including a tissue collection device extending means and a distal section including a tissue collection device, the second removable probe being  
5 configured to fit at least partially within the tubular member to enable the tissue collection device to extend out of and to retract within the second window when the tissue collection device extending means are activated, and a third removable probe, the third removable probe being configured to fit at least partially within the tubular member and including an imaging device mounted therein that is configured to face out of the third window.

10 The present invention may also be viewed as an excisional biopsy system for soft tissue, comprising a tubular member defining a first and a second window near a distal tip thereof; a first removable probe comprising a proximal portion and a distal portion, the proximal portion including a tool extending means, the distal portion including a cutting tool and a tissue collection tool, the first removable probe being configured to fit at least partially  
15 within the tubular member to enable the cutting and tissue collection tools to selectively extend out of and to retract within the first window when the tool extending means are activated, and a second removable probe, the third removable probe being configured to fit at least partially within the tubular member and including an imaging device mounted therein that is configured to face out of the second window.

20 The cutting and tissue collection tools may be mechanically coupled to one another. The cutting and tissue collection tools may also be independently activated and the tool extending means may include a cutting tool extending means operative to extend and to retract the cutting tool out of and into the first window and a tissue collection extending



means operative to extend and to retract the tissue collection tool into and out of the first window.

## BRIEF DESCRIPTION OF THE DRAWINGS

5 For a further understanding of the objects and advantages of the present invention, reference should be made to the following detailed description, taken in conjunction with the accompanying figures, in which:

Fig. 1A shows an embodiment of the excisional device according to the present invention with the cutting tool in its flat, retracted configuration.

10 Fig. 1B shows the excisional device of Fig. 1A with its cutting tool in an extended, bowed configuration.

Fig. 1C shows another view of the excisional device of Fig. 1A.

Fig. 2A depicts the distal region of another embodiment of the excisional device according to the present invention, showing the excisional device together with the external  
15 tissue collection attached thereto in the open configuration.

Fig. 2B shows the excisional device of Fig. 2A together with the external tissue collection attached thereto in the closed configuration.

Fig. 2C shows an embodiment of the proximal region of the excisional device according to the present invention.

20 Fig. 3A depicts the operation of an embodiment of the excisional device and method according to the present invention.

Fig. 3B further shows the operation of an embodiment of the excisional device and method according to the present invention.

Fig. 3C further depicts the operation of an embodiment of the excisional device and method according to the present invention.

5 Fig. 4 shows a detailed view of a cutting tool suitable for use with the excisional device according to the present invention.

Fig. 5 shows a cross section of the cutting tool, taken along line AA' in Fig. 4.

Fig. 6 shows a detailed view of another cutting tool suitable for use with the excisional device according to the present invention.

10 Fig. 7 shows a cross section of the cutting tool, taken along line BB' in Fig. 6.

Fig. 8 shows another embodiment of a cutting tool suitable for use with the excisional biopsy device according to the present invention.

Fig. 9 is a cross-sectional schematic of the tubular member 110, to illustrate the relative placements of the cutter window 120 and of the transducer 270 about the circumference of the tubular member 110. Unnecessary details have been omitted for clarity.  
15

Fig. 10 shows an excisional device according to another embodiment of the present invention, in which the tubular member of the excisional device includes an internal lumen through which a removable transducer core may be inserted.

Fig. 11 shows an embodiment of a removable transducer core according to the present invention.  
20

Fig. 12 shows a cross section of the embodiment of the excisional device of Fig. 10, taken along line AA'.

Fig. 13 shows the removable transducer core of Fig. 11 inserted within an expandable sheath, according to a further embodiment of the present invention.

Fig. 14 shows another embodiment of a soft tissue excisional device assembly according to the present invention, in which a removable transducer core is inserted and  
5 secured within the excisional device so that the active element faces out of the transducer window.

Fig. 15 shows another embodiment of a cutting tool (and method of making same) that is suitable for use within the excisional device according to the present invention.

Fig. 16 shows a view of the completed cutting tool of Fig. 15.

10 Fig. 17 shows an embodiment of the method of excisional biopsy method according to the present invention.

Fig. 18 is a top view of a removable cutting probe, according to an embodiment of the present invention.

Fig. 19 is a side view of the removable cutting probe of Fig. 18, showing the  
15 adjustable window slide in a first position, according to an embodiment of the present invention.

Fig. 20 is a side view of the removable cutting probe of Fig. 18, showing the adjustable window slide in a second position, according to an embodiment of the present invention.

20 Fig. 21 is a top view of a removable tissue collection probe, according to an embodiment of the present invention.

Fig. 22 is a detail view of a removable tissue collection probe of Fig. 21.

Fig. 23 is a side view of the removable tissue collection probe of Fig. 21, showing the tissue collection device thereof in an extended (bowed) configuration.

Fig. 24A is a top view of a removable cutting and tissue collection combination probe, according to an embodiment of the present invention.

5        Fig. 24B is a partial cross-sectional view of the removable cutting and tissue collection combination probe of Fig. 24A, taken along lines AA'.

Fig. 25 is a top view of a removable cutting and tissue collection combination probe, according to another embodiment of the present invention.

10        Fig. 26 is a side view of a removable cutting and tissue collection combination probe, according to a still further embodiment of the present invention, wherein the cutting device and tissue collection devices are shown in their extended configuration.

Fig. 27A is a partial cross-section of a tissue collection probe, taken at the level of the tissue collection device thereof, wherein the tissue collection device is in its initial, non-extended configuration.

15        Fig. 27B is a partial cross-section of a tissue collection probe of Fig. 27A, wherein the tissue collection device is in its extended configuration.

Fig. 27C is a partial cross-section of a tissue collection probe of Fig. 27B, wherein the tissue collection device has returned to its non-extended configuration after capturing the target tissue.

20        Fig. 28 is a flowchart of a soft tissue treatment method, according to another embodiment of the present invention.

## DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1A, 1B and 1C show an embodiment of the distal region 105 of the excisional biopsy device 100 according to the present invention. Considering Figs 1A, 1B and 1C collectively, the distal region 105 of the excisional biopsy device 100 includes a generally tubular member 110 having a generally tapered distal tip 115. The distal tip 115 is configured to penetrate soft tissue, such as breast tissue, lung tissue, liver tissue and the like. Preferably, therefore, the distal tip 115 and the distal region 105 of the excisional biopsy device 100 present a smooth, and relatively atraumatic profile to the soft tissue in which it is designed to penetrate. Alternatively, the tip 115 may be sharply pointed and/or may include an energy source (not shown) to facilitate cutting through the tissue. The tubular member 110 may be formed of rigid and hard plastic, or may be made of stainless steel, for example. Preferably, the tubular member 100 is used once and disposed of, for both safety and functional reasons.

A cutter window 120 is disposed within the tubular member 110. The cutter window 120 may be, for example, a shallow trench formed in the tubular member 110. As best seen in Fig. 1C, the cutter window 120 may be a shallow and substantially rectangular trench in the tubular member 110, or may be, for example, a thin, shallow I-shaped trench. The excisional biopsy device 125 includes a work element, such as a cutting tool 125. The distal end of the cutting tool 125 is attached to the tubular member 110 near its distal tip 115. For example, the distal end of the cutting tool 125 may be attached to the distal-most point 121 of the cutter window 120. The cutting tool 125, however, may alternatively be attached to other points within the distal region 105. The distal portion of the cutting tool 125 is exposed through the cutter window 120. The remaining portion of the cutting tool 125 is disposed

within an internal guide or lumen 130 of the generally tubular member 110. The internal guide 130 constrains the movement of the cutting tool 125 and allows the cutting tool 125 to freely slide therein, parallel to the longitudinal axis of the tubular member 110. With particular reference now to Fig. 2C, the proximal portion 225 of the cutting tool 125 emerges from the internal lumen 130 near the proximal end 215 of the tubular member 110. The proximal end of the cutting tool 125 may, for example, include a push or turn knob 226. The push or turn knob 226 allows the operator of the excisional biopsy device 100 to selectively push the cutting tool 125 in the distal direction (away from the physician and toward the distal tip 115) or retract the cutting tool 125 in the proximal direction (toward the physician and away from the distal tip 115). To assist in controlling the movement of the cutting tool 125, the cutting tool is preferably biased in the proximal direction, as symbolized by the arrow 227 in Fig. 2C. This biasing may be effectuated by means of a spring 228 attached at or near the proximal end 215 of the tubular member 110 and to the proximal portion 225 of the cutting tool 125. In this manner, the default configuration of the cutting tool 125 is the retracted position, wherein the cutting tool 125 lies substantially flat within the cutter window 120 of the tubular member 110.

The cutting tool 125, when pushed in the distal direction by the physician applying pressure in the distal direction on the push or turn knob 226 or equivalent structure, slides within the internal guide 130 of the tubular member 110. As the distal end of the cutting tool 125 is attached near the distal end of the tubular member 110 or to the distal-most point 121 of the cutter window 120, the portion thereof exposed through the cutter window 120 tends to bow outwardly, extending out of the cutter window 120, as shown in Fig. 1B. The extension out of the cutter window 120 and the degree of bowing may be controlled by the physician,

by appropriate action on the push or turn knob 226. Thus, the possible range of extension and bowing is potentially infinite, being limited only by the physician's ability to control the cutting tool 125 by finely pushing and retracting the push or turn knob 226. The degree of extension, as well as the shape of the bowed portion of the cutting tool, therefore, may be controlled by selectively sliding the cutting tool within the internal guide 130 of the tubular member 110.

The shape of the bowed portion and the ease with which the distal portion of the cutting tool 125 bows outwardly may be varied by varying the physical characteristics of the cutting tool 125. Preferably, the cutting tool is formed of a resilient, readily deformable material that, when unstressed, returns to its original unbiased configuration. For example, a nickel titanium alloy may be used for the cutting tool 125, to allow the cutting tool 125 to exhibit shape-memory characteristics. The shape of the cutting tool 125 in its bowed and extended configuration (Fig. 2) may be further controlled by varying, for example, the thickness of the cutting tool over the portion thereof exposed through the cutter window 120. A locally thicker portion of the cutting tool 125 will not bend as readily as a locally relatively thinner portion thereof. Judiciously varying the thickness, for example, of the cutting tool 125, therefore, allows the curvature of the bowed portion thereof to be controlled.

As shown in Figs. 1A, 1B, and with reference to Fig. 1C, pushing on the push or turn knob 226 (or any such functionally equivalent structure) causes the cutting tool 125 to bow outwardly and extend out from the cutter window 120 of the tubular member 110, as shown in Fig. 1B. Similarly, retracting the push or turn knob 226 (or any such functionally equivalent structure) causes the cutting tool 125 to flatten out within the cutter window 120 and to assume a configuration (shown in Fig. 1A) that may be substantially flush with the

outer surface of the tubular member 110. In this configuration, the tubular member 110 may easily penetrate soft tissue, such as breast, lung, liver or other soft body tissue.

In operation, the surgeon makes an incision into the patient's skin, such as the surface of the breast. The excisional biopsy device 100 then may be directly introduced into the breast tissue, or an expandable sheath (shown at reference numeral 495 in Fig. 13) may be introduced into the incision and thereafter expanded as the excisional biopsy device 100 is introduced therein. In any event, the excisional biopsy device is introduced into the breast tissue itself and positioned, for example, adjacent to the lesion in the breast or adjacent the target site from which the excision is to take place. During the introduction of the excisional biopsy device 100 into the soft tissue, the cutting tool 125 is in its retracted configuration wherein the portion thereof exposed through the cutter window 120 is substantially flat. The excisional device 100, in this configuration, therefore, exhibits a smooth and tapered profile to the surrounding tissue. Once the device 100 has been determined to have been properly positioned within the soft tissue, the device is rotated about its longitudinal axis. The rotation may be carried out manually, or the rotation of the device may be carried out by a motorized unit disposed within the proximal region of the device 100. As the device 100 rotates, the surgeon causes the cutting tool 125 to bow outwardly and to extend from the cutter window 120. Preferably, the degree of bowing and outward extension is at least sufficient to include the lesion (such as the targeted microcalcification within the breast) within the space between the cutter window 120 and the cutting tool 125. The cutting tool 125 cuts the tissue as the device 100 is rotated, thereby severing the lesion from its surrounding breast tissue mass. By completing at least one revolution within the breast tissue, the cutting tool 125 sweeps a volume of revolution of breast tissue and severs that



volume from the main tissue mass. Such volume of revolution includes at least the targeted lesion. Preferably, the volume of revolution severed from the main tissue mass not only includes the targeted lesion, but also includes a margin of healthy tissue surrounding the lesion. The degree of extension and bowing of the cutting tool 125 may be varied within a given revolution of the excisional biopsy device 100. In this manner, it is possible to exert fine control over the amount of tissue cut away from the main tissue mass, as well as fine control over the shape of the severed mass.

After the lesion and preferably a margin of healthy tissue around the lesion have been severed, the severed tissue may be removed from the main tissue mass. This removal of the severed tissue may be effectuated by any number of means, including the retraction of the excisional biopsy device 100 from the main tissue mass. Alternately, severed tissue extraction may be carried out by means of the structure and method to be described below.

The cutting tool 125 may, as shown in Fig. 1C, be configured as a thin ribbon. The thin ribbon 125 shown in Fig. 1C is preferably sharpened on its leading edge to facilitate cutting through tissue and sometimes fibrous and calcified masses. The leading edge of the cutting tool 125 is that edge thereof that first comes into contact with the tissue to be severed as the device 100 is rotated. Such a sharpened leading edge is shown in Fig. 4 at reference numeral 127. The width of such a ribbon cutting tool 125 is preferably smaller than the width of the cutter window 120 into which it recedes when the cutting tool 125 is retracted in the proximal direction.

Another embodiment of the cutting tool 125 is shown in Fig. 8. To decrease the forward resistance of the cutting tool 125 as it slowly cuts through tissue, the leading edge of the portion thereof exposed through the cutter window 120 may be serrated, including a

plurality of teeth 127. In turn, the leading edge of the plurality of teeth 127 may include a sharpened edge. In this manner, as the excisional device 100 rotates, only the forward-most tips of the teeth 127 will initially come into contact with the tissue to be cut, thus reducing the tissue surface upon which the force of the rotating cutting blade 125 is applied. Thus, the cutting blade 125 of Fig. 8 is believed to be highly effective in cutting through even relatively dense or fibrous tissue while minimizing the torque to be applied to the excisional biopsy device 100 as it is caused to rotate within the main soft tissue mass.

Referring to Fig. 4 and also to Fig. 5, the cutting tool 125 may further comprise an interior lumen 128 running an entire length or a portion of the length of the cutting tool 125. The cutting tool 125 may further include a plurality of through holes 126 in the distal portion of the cutting tool 125 exposed through the cutter window 120. The plurality of through holes 126 are in fluid communication with the internal lumen 128. In use, the internal lumen 128 may be connected, in the proximal portion of the excisional biopsy device 100, to a fluid reservoir. The fluid reservoir, which may be internal or external to the proximal section of the device 100, supplies the distal portion of the cutting tool 125 with, for example, anaesthetic (such as, for example, lidocaine) and/or antibiotic fluid. In this manner, such anaesthetic and/or antibiotic fluid (or other fluid) may be delivered precisely to the tissue surrounding the cutting tool 125 as it rotates. A precisely dosed anaesthetic, for example, may be delivered to the very site where it is most needed. As such anaesthetic is delivered only where it is needed, the effect thereof is near instantaneous, and the patient feels little or no pain as the excisional biopsy device 100 according to the present invention is rotated within her breast, or other soft tissue. Fig. 5 shows a cross-section of the cutting tool 125 of Fig. 4, taken along line AA' in Fig. 4.

Care should be exercised in selecting the configuration and materials for the cutting tool 125 shown in Figs. 4 and 5. Indeed, the configuration and materials selected should allow the cutting tool 125 to bow and extend out of the cutter window 120 of the device 100 without, however, pinching or substantially disrupting the flow of fluid delivered via the internal lumen 128 of the cutting tool 125, if the cutting tool 125 is provided with such. For example, the cutting tool 125 may be made of a shape-memory metal, such as nickel-titanium and/or the proximal portion of the cutting tool 125 may be formed relatively thicker than other portions thereof.

Another embodiment of the cutting tool 125 is shown in Figs. 15 and 16. As shown therein, the cutting tool 125 may be formed by a thin sheet of steel or shape memory alloy. The sheet may include a plurality of through holes 126 to allow the anaesthetic or other fluid to be instilled therethrough. A small tube 540 may be disposed on the sheet, aligned with the through holes 126. The sheet may be folded in the direction indicated by the arrows 530, thus securing the tube 540 between the two folded sides of the sheet. The edges 550 of the sheet may be sealed together to render them fluid tight. For example, the sides 550 of the sheet may be welded together or secured by other means known to those of skill in the metal working arts. The edges 560 between the through holes 126 may be sharpened, to allow the cutting tool 125 to efficiently cut through soft tissue. As shown in Fig. 16, the tube 540 may deliver anaesthetic or other fluid to the cutting tool 125, which delivers minute amounts thereof precisely where it is needed: where the cutting edges 560 of the cutting tool 125, thereby affording the patient immediate relief and minimizing the amount of anaesthetic that need be delivered. The proximal end of the tube 540 may be in fluid communication with an anaesthetic reservoir (not shown) and/or an anaesthetic pump (also not shown).

Alternatively, the cutting tool 125 may include a thin wire, such as shown at 125 in Figs. 6 and 7. In this case, an external radio frequency (hereafter, RF) power source 240 (shown at 240 in Fig. 2C) supplies the cutting tool 125 with RF energy via two bipolar electrodes (not shown) attached to the cutting tool 125 of Fig. 6. Other energy sources may also be used within the context of the present invention, RF power being discussed herein for illustrative purposes only. The RF power delivered by the RF power source 240 allows the cutting tool 125 of Fig. 6 to become an electrosurgical cutting and/or an electrocoagulating tool by selectively varying the power applied to the cutting tool 125. Suitable generators for such an electrosurgical cutting device 125 are known to those of skill in this art. An example of such a suitable generator is described in U.S. patent 4,903,696 issued Feb. 27, 1990 and assigned to Everest Medical Corporation, Brooklyn Center, Minn., the disclosure of which is incorporated herewith in its entirety. As with the cutting tool 125 shown in Figs. 4 and 5, the cutting tool 125 of Figs. 6 and 7 includes an internal lumen 128 and a plurality of through holes 126 to allow anaesthetic or other fluid to be delivered to the surrounding tissue as the cutting tool 125 cuts through the soft tissue as the device 100 is rotated.

As alluded to above, the excisional biopsy device 100 according to the present invention cuts out a (not necessarily symmetrical) volume of revolution as it cuts through the soft tissue upon rotation of the generally tubular member 110. This severed mass of tissue may be stabilized using an extendable tissue anchoring device, which anchoring device also assists in the retrieval of the severed tissue sample from the breast. The anchoring device may, for example, include a suction device or other substantially rigid anchor member to anchor the tissue sample. Alternatively, the severed tissue sample may be collected in a tissue collection device, as shown at reference numeral 260 in Figs. 2A and 2B. The tissue

collection device 260 is attached externally to the tubular member 110, and preferably also to the trailing edge of the cutting tool 125. The tissue collection device 260 is preferably formed of a thin and flexible plastic membrane shaped like a bag. The opening of the bag-shaped collection device 260 is preferably co-extensive with the opening 120 and is preferably attached to the tubular member 110 and to the trailing edge of the cutting tool 125. In this manner, the opening or "mouth" of the bag-shaped collection device 260 opens and closes along with the bowing and retraction, respectively, of the cutting tool 125. Indeed, the "mouth" of the bag-shaped collection device 260 is opened when the cutting tool 125 is bowed and extended out of the cutter window 120 and substantially closed when the same is retracted within the cutter window 120, as the two edges (one attached to the tubular member 110 just adjacent to the edge of the cutter window 120 and the other attached to the trailing edge of the cutting tool 125) of the collection device are then pressed together.

Therefore, when the excisional device 100 is inserted into soft tissue and rotated, the cutting tool 125 may be caused to bow and to extend outwardly from the cutter window 120 and caused to cut tissue coming into contact therewith. As the device 100 rotates and cuts, the tissue between the cutting tool 125 and the tubular member 110 tends to advance toward and into the collection device. As the cutting tool 125 is in it's bowed and extended state, the "mouth" or opening of the bag-shaped collection device 260 is also correspondingly open, allowing the severed tissue to collect therein. As the revolution of the tubular member 100 is completed, the cutting tool 125 may be retracted and caused to assume a configuration wherein it is disposed within the recessed cutter window 120, substantially flush with the outer surface of the tubular member 110, as shown in Fig. 2B. In this configuration, the collection device 260 is closed, thereby securing the excised tissue sample therein. The

device 100 may then be safely retracted from the main tissue mass, such as the breast. As the excised sample is physically isolated from the remaining tissue mass, the probability of seeding the surrounding tissue with potentially abnormal cells is markedly decreased. This probability is also further decreased, as the excisional device 100 according to the present invention allows the surgeon to obtain adequate margins of healthy tissue surrounding the target lesion by choosing the degree of bowing and extension of the cutting tool 125. In this manner, the integrity of the lesion itself is not violated, thereby maintaining tissue architecture intact.

As the collection device 260 is preferably formed of a thin and flexible membrane, it is able to lay substantially flat against the outer surface of the tubular member 110 or slightly recessed within the cutter window 120 during insertion thereof into the soft tissue. The collection device 260, therefore, offers little additional drag and resistance to the device 100 as it is inserted into the incision made in the patient's skin during or prior to the procedure. Suitable materials for the tissue collection device 260 include plastics and nylon, for example. Any strong adhesive may be utilized to secure the tissue collection device 260 to the tubular member 110 and to the cutting tool 125. Other means of securing the collection device 260 may also be employed without, however, departing from the scope of the present invention. Likewise, the tissue collection device 260 may be formed of a material other than specifically enumerated herein while remaining within the spirit of the present invention. Preferably, the shape and size of the tissue collection device 260 are such as to minimize drag on the excisional biopsy device 100 as it is inserted and rotated into the tissue. For example, the tissue collection device 260 preferably should be only as large as necessary to contain the excised tissue sample.

The excisional biopsy device 100 according to the present invention is preferably accurately positioned adjacent to the lesion within the breast or other organ. Toward that end, the present invention allows the surgeon to gain near real time or real time information as to the internal structure of the soft tissue during the procedure itself. Referring now back to Figs. 1 and 2C, the present invention may include a transducer 270 mounted within the distal portion of the tubular member 110. This transducer 270 is preferably adapted to image tissue about to be cut by the cutting tool 125 as the excisional biopsy device 100 is rotated within the soft tissue. Indeed, the transducer 270 preferably generates information relative to the tissue about to be cut – that is, tissue that has not yet been brought into contact with the cutting tool 125 as the tubular member 110 rotates about its longitudinal axis. In this manner, as the rotational speed of the excisional biopsy device 100 is preferably quite slow (the rotation may be manually carried out or may be caused by a slow moving motorized unit attached to the tubular member 110), the surgeon may evaluate the information generated by the transducer 270 and may, based upon this information, vary the degree of bowing and extension of the cutting tool 125. For example, when the device 100 is positioned adjacent to the lesion of interest and rotated, the transducer 270 will detect the presence and location of the lesion before the lesion comes into contact with the cutting tool 125. After the lesion has been detected by the transducer 270, the surgeon may push on the push or turn knob 226 or other structure that causes the cutting tool to bow and extend from the cutter window 120. The lesion (and preferably an adequate margin of healthy tissue) will then be severed from the main mass, and optionally collected, for example, in the tissue collection device 260. When the transducer 270 indicates that the rotation of the tubular member has brought the cutting tool 125 past the lesion, the cutting tool 125 may be retracted within the cutter

window 120. The cutting, it can be seen, may be specifically tailored to the size and shape of the lesion within the main tissue mass in near real time or in real time, thereby allowing the surgeon to excise all of the tissue required and only the tissue that is necessary to achieve the intended results.

5 Preferably, the transducer 270 is an ultrasound sensor mounted substantially flush with the external surface of the tubular member 110. The ultrasound sensor 270 is preferably electrically connected, via a communication channel such as electrical conductors, to at least one data processing and display device, shown at reference 250 in Fig. 2C. The data processing and display device(s) 250 allows the surgeon to see, in near real time or in real  
10 time, the internal structure of the tissue about to be cut by the cutting tool 125. This allows the surgeon not only to see a graphical representation of the internal structure of the tissue during the procedure itself, but also allows the surgeon to assure himself or herself that the entire lesion or group of lesions has been properly excised by, for example, rotating the tubular device within the tissue while the cutting tool is retracted within the cutter window  
15 120 while the transducer 270 is energized. Viewed from another aspect, therefore, the present invention is an intra-tissue ultrasound imaging device that may, but need not include a cutting tool, such as referenced by numeral 125 in the figures.

In operation, the (e.g., ultrasound) transducer sweeps a plane (graphically shown at 280 in Fig. 3A) within the tissue ahead of the work element, such as cutting tool 125. In  
20 selecting the operational characteristics of the ultrasound transducer 270, the surgeon must balance the required resolution (i.e., the smallest feature that must be discernable) with the degree of penetration of the ultrasound waves within the tissue and the intensity of the ultrasonic waves generated. In general, higher frequencies allow better resolution. However,



high frequencies do not penetrate the tissue as far as do lower frequency ultrasound waves. Preferably, the ultrasound transducer 270 is tuned within the range from about 5 MHz to about 20 MHz. More preferably, the ultrasound transducer 270 is tuned within the range of about 7.5 MHz to about 20 MHz. For example, in the case wherein the excisional biopsy  
5 device 100 according to the present invention is used within the female breast, the ultrasound transducer may be tuned within the range of about 10 MHz to about 13 MHz.

To effectively image the internal tissue structure prior to cutting it with, for example, the cutting tool 125, the transducer 270 must be positioned within the tubular member 110 away from the cutting tool 125. With reference to Fig. 9, the transducer 270 may be disposed  
10 within the tubular member at an angle  $\alpha$  relative to the cutting tool 125. The angle  $\alpha$  is preferably no smaller than that necessary to effectively control the operation of the work element (such as cutting element 125) in response to information gathered from the transducer 125 as the tubular member 110 rotates. This angle  $\alpha$ , therefore, is dependent at least upon the rotational speed imposed upon the tubular member 110 and upon the time  
15 necessary for the surgeon to assimilate the information generated by the transducer and to effectively control the cutting tool 125 in response to such information. Preferably, the angle  $\alpha$  is less than about 180 degrees.

When used in conjunction with an intra-tissue ultrasound transducer, such as shown at 270, the excisional biopsy device 100 according to the present invention may include a  
20 variety of work elements in place of or in addition to the cutting tool 125. Such work elements include, for example, an abrasive device, a reciprocating cutting device, an electrosurgical device or a vibrating device.

In the case of lesions within the breast, it is useful to stabilize the breast prior to imaging and performing invasive procedures. Such stabilization is conventionally performed by compression plates that squeeze the breast and compress the tissue therein. Such compression is necessary to allow x-ray radiation, as used in mammography, to produce a useful image. Although such compression is not needed or believed to be desirable according to the present invention, stabilization of the breast remains necessary. For this purpose, the breast stabilization devices described in commonly assigned U.S. patent applications 09/158,215 entitled "Breast Stabilization Devices And Methods" filed on September 22, 1998, and 09/200,661 entitled "Breast Stabilization Devices And Imaging And Interventional Methods Using Same" filed on November 25, 1998, the disclosures of each being incorporated herein in their entirety, may be useful.

Reference is now made to Figs. 3A, 3B and 3C, which illustrate an embodiment of the excisional biopsy method according to the present invention. Although Figs. 3A-3C illustrate an embodiment of the present invention within the context of breast surgery, it is to be understood that the present inventive method is equally applicable to other soft tissue masses, such as, for example, lung, thyroid or liver tissue, with only minor modifications that will become apparent to skilled practitioners in this art.

Turning first to Fig. 3A, a small incision 331 is made in the breast 310, preferably in the peri-areolar region. Preferably, the breast is stabilized, using, for example, the breast stabilizing devices disclosed in U.S. patent applications 09/158,215 or 09/200,661 referred to above. The portion of the device 100 that remains outside of the soft tissue may include attachment means (not shown) for clamping the device to a rim structure, for example, to allow stable operation and precise guidance thereof. The small incision is preferably made

on the border of the areola 330 surrounding the nipple 320, as this provides a better cosmetic scar than on the skin on the side of the breast 310. Depending on the size of the lesion and the size of the excisional biopsy device 100 to be inserted therein, an expandable sheath (an example of which is shown at reference numeral 495 in Fig. 13) may be inserted into the breast tissue. In any event, the excisional biopsy device 100 is inserted into the breast tissue and positioned adjacent the lesion 300, which may be, for example, a microcalcification or other abnormal lesion. Once in position, the device 100 is rotated, for example, in the direction indicated in Fig. 3A. The portion of the excisional biopsy device 100 that remains outside the soft tissue may have a greater diameter than the portion thereof that is designed to penetrate the soft tissue. This aids in manual rotation of the device 100. In the configuration depicted in Fig. 3A, the cutting tool 125 is retracted within the cutter window 120 and the tissue collection device 260, if present, is substantially flat against the external surface of the tubular member 110. The device 110 is rotated about its longitudinal axis and the transducer 270 is energized, the information therefrom being transmitted to, for example, the display device 250 shown in Fig. 2C. When the lesion 300 comes into view, the surgeon then gauges the size, shape and location thereof and controls the bowing and extension of the work element, such as cutting tool 125 based on the information received from the transducer 270 and displayed upon the display 250. Fig. 3B depicts the situation wherein the lesion 300 has been imaged and the surgeon has extended the cutting tool 125 to sever the lesion 300 from the surrounding breast tissue. The severed tissue may be received and collected in a tissue collection device 260, as the device 100 rotates. Anaesthetic and/or antibiotic (or other) fluids may be delivered directly to the affected tissue by through holes 126 (best seen in Figs. 2A, 2B and Figs. 4-7), greatly decreasing pain during the procedure

After the lesion and any desired margin of healthy tissue is severed from the main breast tissue mass, the cutting tool 125 is retracted within the cutter window 120. This closes the tissue collection device 260, if present, and allows the entire device 100 to be retracted from the breast in the direction of arrow 350, as shown in Fig. 3C. If the tissue collection device 260 is present, the lesion 300 will be isolated from surrounding tissue by the membrane of the tissue collection device 260, thus minimizing any possibility of seeding potentially abnormal cells to surrounding breast tissue. Moreover, the tissue architecture of the retrieved lesion 300 is substantially preserved, thereby allowing accurate histopathology to be performed upon the entire mass excised from the breast. Indeed, any compression such tissue may undergo is believed to be solely due to the retraction of the device back through the entrance track of the device 100 in the uncompressed breast tissue. Thereafter, when the excisional device 100 is removed from the breast 310, the push or turn knob 226 may be acted upon to extend and bow the cutting tool 125, thereby allowing the excised lesion to be retrieved from the tissue collection device 260 for examination. If the tissue collection device is not present, conventional suction means may be employed to extract the severed lesion from the surrounding breast tissue. Bleeding is controlled by suitably varying the RF or other power source applied to the electrosurgical cutting tool 125, if present, to stem the bleeding by cauterizing the tissue coagulating the blood.

After the procedure, a small cavity remains in the breast where the lesion had previously been. However, since no compression of the breast was carried out, no expansion of the tissue occurs after the procedure, unlike conventional techniques. Therefore, the cavity and the entrance and exit path of the device remain as small as possible, leading to fewer complications, less tissue trauma and improved aesthetics.

According to another embodiment of the present invention, shown in Figs. 10, 11 and 12, the transducer 270 is replaced by a removable transducer core 400. The removable transducer core 400 includes an active element 440 configured to perform intra-tissue imaging and of relaying information back to a display device (shown in Fig. 14) via a communication channel, such as shown at reference numeral 460. The communication channel 460 may be wireless or may include, for example, optical fibers and/or electrical conductors. The active element 440 may draw power from an internal battery (not shown) or from a power source, such as shown at reference numeral 480. The active element 440 may include an ultrasound transducer. Other types of transducers may be used instead of or in addition to an ultrasound transducer. The removable transducer core 400 preferably includes a generally tubular shaft 430. A proximal section 450 is included near the proximal portion of the transducer core 400.

To accommodate the removable transducer core 400, the excisional device 100 of Fig. 10 defines an internal lumen 420 through which the removable transducer core 400 may be inserted. Preferably, the excisional device 100 is used once and disposed of, for safety and functional reasons. The removable transducer core 400, however, may either be disposable or re-usable for a limited number of uses. To allow the active element 440 of the transducer core 400 to image the lesion to be excised and the surrounding tissue, the generally tubular member 110 of the excisional device 100 includes a transducer window 410. When the removable transducer core 400 is inserted within the internal lumen 420, the proximal section 450 of the core 400 preferably snaps into a locked configuration with the proximal end of the excisional device 100. When in its locked configuration, the active element 440 of the transducer core 400 is aligned with and faces the transducer window 410, to allow the active

element 440 to image the lesion and the surrounding tissue therethrough. To facilitate insertion of the tubular member 110 in the patient's soft tissue the distal-most tip thereof may include an (mono or bipolar) RF electrosurgical element or wire, as indicated at reference numeral 116, which may be energized by an RF source, as shown at 240 in Figs. 2C and 14.

5 Fig. 11 shows an embodiment of the removable core 400 according to the present invention. As the removable core 400 may advantageously be used independently of the excisional device 100, the removable core 400 includes a distal tapered tip 470, to allow it to easily penetrate soft tissue. Moreover, its thin profile allows the surgeon to insert the removable core 400 within soft tissue without, however, unduly damaging the tissue or  
10 making a large incision. The removable core 400 allows the surgeon to precisely localize the lesion to be excised from within the tissue itself. For example, the active element 440 of the removable core 400 may include an ultrasound transducer having similar characteristics as the sensor 270, and may be used alone or in addition to surface ultrasound to localize the lesion with a great degree of precision.

15 Fig. 12 shows a cross section of the embodiment of the excisional device 100 of Fig. 10, taken along line AA'. As shown in Fig. 12, the cutting tool 125 is exposed through the cutter window 120. The window 120 may, as shown in Fig. 12, include support guides 122 to support and guide the cutting tool 125 as it is outwardly extended and bowed. The tissue collection device 260, for clarity, is not shown in either Figs. 10 or 12. However, to  
20 accommodate the bulk of the excised tissue sample collected in the tissue collection device 260 after the cutting and collecting operation described herein, the tubular member 110 may include a recessed section 131. The recessed section provides space for the collected (e.g., bagged) tissue sample in the tissue collection device 260 when the excisional device is

removed from the soft tissue mass. In this manner, the collected tissue sample within the tissue collection device 260 does not protrude from the generally smooth outer surface of the excisional device 100 upon retraction of the latter from the soft tissue mass from which the tissue sample is excised. The internal lumen 420 allows the removable core 400 to slide  
5 therein and to properly position the active element 440 facing the transducer window 410.

Fig. 13 shows the removable core 400 inserted within an expandable sheath 495. The expandable sheath includes a proximal base section 510. Attached to the proximal base section 510 is a generally cylindrical expandable meshwork 500 of, for example, plastic or nylon fibers. The meshwork 500 may be somewhat tapered at its distal end 520, to provide a  
10 smooth transition between the expandable meshwork 500 and the removable core device 400. The proximal section 450 of the core 400 may snap-fit to the proximal base section 510 of the expandable sheath 495, so as to be securely and removably attached thereto. As shown in Fig. 13, the expandable meshwork 500 expands just enough to accommodate the removable core 400 inserted therein. In practice, the expandable sheath 495 and removable core 400  
15 assembly may be inserted within the soft tissue together, to allow the surgeon to image the lesion prior to inserting the somewhat greater diameter excisional device 100 therein. Thereafter, the surgeon may retract the removable core 400 from the expandable sheath 495, leaving the expandable sheath 495 in place within the soft tissue, such as the breast.

Fig. 14 shows another embodiment of a soft tissue excisional device assembly 600  
20 according to the present invention. In the configuration shown in Fig. 14, the removable core 400 is inserted and secured within the excisional device 100 so that the active element 440 faces out of the transducer window 410. As in Fig. 10, the tissue collection device 260 is not shown, for clarity. In Fig. 14, the excisional device 100 is shown inserted within the

expandable sheath 495. Indeed, the excisional device 100, in Fig. 14, is shown inserted within and past the distal end 520 of the meshwork 500, so the distal portion of the excisional device 100 including the cutting tool 125 and the transducer window 410 extends therethrough. The meshwork 500, in Fig. 14, has expanded to accommodate the diameter of the excisional device 100. The proximal portion of the excisional device 100 may extend from the proximal base section of the expandable sheath 495. This allows the push or turn knob 226 (a turn knob 226 shown in Fig. 14) to be manually accessible to the surgeon. A number of peripheral devices may be connected to the assembly 600. Examples of such include a core power source 480, which may be, for example, an electrical source for an ultrasound transducer, one or more data processing and display devices 250 on which the internal structure of the tissue imaged by the active element 440 of the core 400 may be displayed, suction means 490, a cutting tool power source (a variable RF energy source, for example), and/or other devices 590. The suction device 490 may provide a suction force to the window 120 through an internal lumen to facilitate cutting of the tissue by the cutting tool 125.

The excisional device assembly 600 may be rotated in toto, or the excisional device 100 may be rotated independently of the expandable sheath 495, depending upon the degree of friction between the two. Preferably, the excisional device 100 is removable from the expanded sheath 495 shown in Fig. 14, while leaving the expanded sheath 495 in place within the soft tissue. In this manner, after retraction of the excisional device 100 from the sheath 495, the sheath 495 remains in place within the soft tissue to allow other instruments to be inserted therethrough. For example, the removable core 400 may, after the excisional procedure proper, be re-inserted through the expanded sheath 495 to the excision site.



Thereafter, the surgeon may cause the active element 440 of the removable core 400 to become energized, to image the excision site to insure that the complete lesion has been removed from the soft tissue mass. To do this, the surgeon may rotate the removable core 400 within the expanded sheath 495 while observing the display or displays for signs of the lesion. If none is found, it is probable that the entire lesion has been successfully removed and the surgeon may then retract the core 400 from the sheath 495 and the sheath from the tissue mass and repair the incision made prior to inserting the assembly therein. Alternatively, the surgeon may choose to remove both the expanded sheath 495 and the core 400 simultaneously.

Fig. 17 shows an embodiment of the method of excisional biopsy method according to the present invention. In Fig. 17, it is assumed that the soft tissue from which the lesion is to be excised is breast tissue and that the active element 440 of the removable core 400 is an ultrasound transducer. Other combinations are possible, and the present invention should not be limited to applications related to breast tissue and ultrasound. The removable core 400 and the active element 440, in Fig. 17, are together abbreviated as "US CORE", a shorthand expression for the phrase "ultrasound core" and the word "assembly" is abbreviated to "Ass'y". Moreover, it is to be understood that the steps shown in Fig. 17 constitute but a broad outline of one possible embodiment of the present inventive method. Therefore, other additional steps may be inserted between the steps shown in Fig. 17, or other steps may be substituted for some of the displayed steps without, however, departing from the scope of the present invention.

The method starts at step S0. In step S1, the lesion within the breast is grossly targeted, using, for example, standard or stereotactic surface ultrasound. In step S1, a rough

estimate of the location of the lesion within the breast is obtained. The surgeon, after having located the general location of the lesion, may mark the location thereof on the ultrasound display or displays and/or on the corresponding surface of the breast, with an "X", for example. The breast is stabilized in step S2. Preferably, the breast is stabilized in an uncompressed or slightly expanded state, in the manner disclosed in the commonly assigned and co-pending US patent application numbers 09/158,215 or 09/200,661 previously discussed and incorporated by reference herein. The woman's other breast is preferably placed within a counterpart breast stabilizing device, which helps to immobilize the woman during the procedure. One of the ultrasound ports of the breast stabilizing device is aligned with the lesion, for example, by aligning one of its ultrasound ports with the marked location on the breast. Suction is then applied to the breast stabilizing device, in the manner described in the above-referenced application and a correctly oriented surface ultrasound device is secured to the ultrasound port of the stabilizing device. Other means of stabilizing the breast may also be used without, however, departing from the present invention.

In step S3, an entry site on the breast is chosen. Preferably, the peri-areolar region is chosen as the incision site, as scars within the peri-areolar region are less visible than scars in more exposed regions of the breast and for other anatomical reasons. The incision site is then anaesthetized, both on the skin surface and subcutaneously. Also in step S3, a small incision is made at the chosen incision site. Preferably, the incision is large enough to accommodate the expandable sheath 495 with the removable core 400 inserted therein. In step S4, the expandable sheath 495, together with the removable core inserted therethrough, is inserted into the incision made in step S3. Under surface ultrasound guidance, for example, the sheath 495/core 400 assembly is navigated adjacent to the lesion. If the sheath 495/core 400

assembly can be properly positioned adjacent to the target lesion, the method according to the present invention proceeds to step S5. If the sheath 495/core 400 assembly cannot be properly positioned adjacent to the target lesion, all or a portion of the above-detailed steps are repeated until proper positioning of the sheath 495/core 400 assembly is achieved,  
5 adjacent to the target lesion.

Assuming now that step S4 has been completed to the surgeon's satisfaction, the core 400 is removed from the expandable sheath 495 and the expandable sheath 495 is left in place within the breast, as shown in step S5. In step S6, the removable core 400 is inserted within the internal lumen 420 of the tubular member of the excisional device 100 and locked  
10 securely in place, so that the active element 440 (in this case, an ultrasound transducer) is aligned with and faces out of the transducer window 410 of the device 100. Again leaving the expandable sheath 495 in place within the breast, the excisional device 100 (with the core 400 secured therein) is advanced through the expandable sheath 495. The sheath 495 then expands within the breast tissue to accommodate the somewhat larger diameter of the  
15 excisional device 100. The excisional device 100 is advanced past the tapered distal end 520 of the sheath 495, so the assembly including the sheath 495, the excisional device 100 and the removable core 400 is positioned adjacent to the target lesion within the breast tissue, as shown in step S7.

In step S8, the correct position adjacent the target lesion and the correct rotational  
20 orientation of the aforementioned assembly (Fig. 14) are confirmed, using surface ultrasound and/or the core ultrasound 400. The active element 440 of the core 400 is particularly well suited for this task, as the excisional device 100 may be rotated within the tissue, and positioned so the cutting tool 125 is properly positioned to allow it to rotate, extend and bow

outwardly in such a manner as to precisely sever the lesion from the surrounding tissue with an adequate margin of healthy tissue. Indeed, the ultrasound transducer 440, as it rotates along with the excisional device 100, images the lesion before the cutting tool 125 cuts it, thereby allowing the surgeon to optimally deploy the cutting tool based upon his or her observation of the imaged tissue on a display or displays. In step 9, the surgeon may activate an anaesthetic infusion, the anaesthetic being delivered by the cutting tool 125 via the plurality of through holes 126, best seen in Figs. 4 and 6. Step S9 may be skipped if the cutting tool 125 does not provide for through holes 126 or if the surgeon does not deem it necessary to anaesthetize the tissue during the rotation of the cutting tool 125. For example, the tissue may have been previously anaesthetized. While rotating at least the excisional device 100 (with the removable core 400 secured therein), the cutting tool 125 is extended using, for example the push or turn knob 226 shown in Figs. 2C and 14, thereby causing the cutting tool 125 to extend from the window 410 and to bow outwardly, as shown in step S10. Depending on the amount of friction between the excisional device 100 and the expandable sheath 495 (which may be freely chosen depending upon the choice of material for the meshwork 500 and the configuration of the mesh), the sheath 495 may rotated along with the excisional device 100. The degree of extension and bowing may be finely controlled by the surgeon as the excisional device 100 is rotated, either manually or by a motorized unit (not shown) coupled thereto. As the cutting tool is rotated, the severed tissue sample is preferably collected (e.g., bagged) in a tissue collection device 260 (Figs. 2A and 2B), as shown at step S11. The blood vessels may be coagulated as the cutting tools rotates and cuts the tissue, or afterwards. In step S12, after the excisional device 100 has completed at least one revolution within the breast and has cut a volume of revolution therein, including at least the target

lesion and preferably a margin of healthy tissue surrounding the lesion, the excisional biopsy device 100 and removable core 400 assembly are retracted through the sheath 495, leaving the sheath 495 once again in place within the breast. Preferably, the tissue collection device 260 and the tissue sample it encloses lie within the recessed section 131 of the generally tubular member 110. In this manner, the filled collection device 260 does not protrude or protrude too much from the surface of the tubular member 110, thereby allowing the retrieved tissue sample to be readily retracted with the excisional device 100 through the sheath 495.

After retraction of the excisional device 100, the core 400 may be retracted from the device 100 and re-inserted through the sheath 495 left in place within the breast. The core 400 is then advanced adjacent to the excision site, and rotated to allow the surgeon to image the excision site to insure that the entire lesion has indeed been removed, as shown in step S13. Some or all of the above steps may be repeated should the imaging of the excision site by the core 400 within the sheath 495 reveal that a portion of the target lesion was not excised. Assuming that the entire target lesion has been removed, the incision is repaired by, for example, suturing the peri-areolar incision site. The method ends at step S16.

The removable transducer core 400 of Fig. 11 is not the only removable probe that may be fitted to and within the tubular member 110 of the excisional device 100 (see Fig. 10, for example). Indeed, Fig. 18 shows a top view of a removable cutting probe 700, according to an embodiment of the present invention. The removable probe 700 includes a proximal portion 702 and a distal portion 704. The proximal portion 702 may include cutting tool extending means 718 and the distal portion 704 may include a cutting tool 706, such as a wire or ribbon cutting tools described above. The cutting tool 706 may be sharpened on its

leading edge. The first removable probe 700 is preferably configured to fit at least partially within the tubular member 110 to enable the cutting tool 706 to selectively bow out of and to retract within a first window 710 when the cutting tool extending means 718 are activated. The first window 710 is defined within the surface of the removable probe 700. According to an embodiment of the present invention, the removable cutting probe 700 may be inserted within the internal lumen 420 (or guided within guides internal to the tubular member 110) of the tubular member 110 in such a manner that the window 710 defined within the probe 700 faces the window 410 (Fig. 10) defined within the surface of the tubular member 110. Alternatively, the tubular member 110 may define one or more additional windows similar to that shown at 410 in Fig. 10. In this case, the removable probe 700 (and those to be described relative to Figs. 21 – 27C) may be inserted within the tubular member 110 such that the window 710 faces one of these additional windows (hereinafter collectively referenced by numeral 410) and/or the window 410 in Figs 10 and 12.

According to an embodiment of the present invention, the cutting tool 706 may include an RF cutting tool. In this case, the RF cutting tool and the removable cutting probe 700 may be connected to an RF power source, such as shown at 240 in Figs. 2C, 14 and 18. The RF cutting tool, for example, may be either a monopolar or a bipolar RF cutting tool, as disclosed above.

The removable cutting probe 700 may also include an internal guide 712 (or may define an internal lumen) to enable the cutting tool 706 to slide within the removable cutting probe 700 when cutting tool extending means 718 are activated. The cutting tools extending means 718 are shown as a thumb-activated dial in Figs. 18-20. However, any other means of advancing and retracting the cutting tool 706 may also advantageously be used within the

context of the present invention. According to a still further embodiment, the distal portion 704 of the removable cutting probe 700 may further include a window slide 708 disposed within the window 710 and the proximal end 702 may further include window slide extending means 716. The window slide 708 is coupled to the window slide extending means 716 and is guided within the removable cutting probe 700 by an internal guide or lumen 714 along the length of the probe 700. According to the present invention, the window slide 708 is configured to selectively cover a portion of the window 710 when the window slide extending means 716 are activated. The window slide extending means 716 are shown in Figs. 18-20 as thumb-activated dials. However, any means of extending the window slide 708 within the window 710 to selectively cover a portion thereof may readily be implemented within the removable cutting probe 700, as those of skill will recognize. Functionally, the window slide 708 covers a portion of the window 710 to selectively vary the width of the window 710 through which the cutting tool 706 is allowed to extend or bow.

The operation of the removable cutting probe 700 is graphically shown in Figs. 19 and 20. Fig. 19 is a side view of the removable cutting probe of Fig. 18, showing the adjustable window slide 708 in a first position, according to an embodiment of the present invention, whereas Fig. 20 is a side view of the removable cutting probe of Fig. 18, showing the adjustable window slide 708 in a second position. As shown in Fig. 19, the window slide 708 is less engaged within the window 710 and it is in Fig. 20. Consequently, the cutting tool 706 in Fig. 19 is able to extend over a wider portion of the window 710 than it is able to when the window slide 708 is in the relatively more engaged position shown in Fig. 20. For example, the window slide 708 may be further engaged within the window 710 (Fig. 20)

when the physician wants to cut a smaller tissue specimen than would otherwise be cut when the probe 700 is in the configuration illustrated in Fig. 19.

Fig. 21 is a top view of a removable tissue collection probe 800, according to an embodiment of the present invention. As shown therein, the removable tissue collection probe 800 includes a proximal section 802 and a distal section 804. The proximal section 802 may include a tissue collection device extending means 814 and the distal section 804 may include a tissue collection device 808, 810. Similar to the removable cutting probe 700 of Figs. 18-20, the removable tissue collection probe 800 may be configured to fit at least partially within the tubular member 110 to enable the tissue collection device 808, 810 to extend out of and to retract within the window 410 (or other window defined within the surface of the tubular member 110) when the tissue collection device extending means 814 are activated. Similar to the activating means 716, 718 of Figs. 18-20, the tissue collection device extending means 814 may be configured as a thumb-dial or a wheel or as any other suitable means for extending the tissue collection device 808, 810, such as a lever, for example. As shown in the top view of Fig. 21 and in the detail top view of Fig. 22, the tissue collection device 808, 810 may include a ribbon or wire 808 that may be configured to extend or bow out of and retract back within the window 806 in the probe 800. Attached to the wire or ribbon 808 is a thin flexible sheet of non-porous or porous material 810, such as polyethylene or polyethylene terephthalate (PET), for example. A non-porous material is preferable to isolate the tissue specimen from the surrounding tissue. Such isolation is used to prevent possible cancer cells from seeding along the insertion track of the probe and/or the excisional device 100. A non-porous flexible material 810 prevents fluid and cell leakage therefrom and insures isolation of the cut tissue specimen. The thin flexible sheet of material



810 may be dispensed from a roll 814 of such material, the free end of the sheet 810 being attached to the ribbon or wire 808. In this manner, the roll 814 may dispense the material 810 as the ribbon or wire 808 is extended or bowed out of the window 806 (and out of a corresponding (facing) window in the tubular member 110) and completely or partially encompass or encapsulate the tissue specimen (see reference numeral 1008 in Figs. 27A-27C) as the tubular member 110 and contained probe 800 are rotated within the patient's soft tissue. Alternatively, the tissue collection device 808, 810 may be configured as shown and described relative to Figs. 2A and 2B, for example. When the tissue collection device extending means 814 are activated, the ribbon or wire 808 slides along the internal lumen or guide 812 defined in the probe 800 and causes the ribbon or wire 808 to bow and extend out of the window 806 defined in the probe 800, thereby deploying the flexible material 810 and encapsulating the tissue specimen. These embodiments allow the tissue specimen to be removed in one piece for best histological analysis by a pathologist. Figs. 27A through 27C show still another tissue collection device configuration, as will be described below.

Fig. 23 shows a side view of the removable tissue collection probe 800 of Fig. 21, showing the tissue collection device 808, 810 in an extended configuration. As shown therein, the tissue collection device extending means 814 has been (manually, for example) activated to cause the bowing of the tissue collection device 808, 810 out of the window 806 defined within the tissue collection probe 800. This bowing, or extension, of the wire or ribbon 808 causes the thin sheet of material 810 to be unrolled or otherwise deployed. As the tubular member 110 of the excisional device 100 is rotated, the tissue collection probe contained therein is also rotated, in the direction shown by arrow 816, for example. The tissue collection device extending means 814 may be activated extended (bowed) so as to

cause the ribbon or wire 808 to follow substantially the same path within the tissue, as did the cutting tool 706. This eases the collection process, as the ribbon or wire 808 merely follows the path of the incision previously made by the cutting tool 706 or 125. As the excisional device is rotated, the tissue specimen (i.e., lesion) is captured within the sheet of material or bag 810, whereupon it may readily be extracted from the patient for pathological examination.

Fig. 24A is a top view of a removable cutting and tissue collection combination probe 900, according to an embodiment of the present invention, whereas Fig. 24B is a partial cross-sectional view of the removable cutting and tissue collection combination probe 900 of Fig. 24A, taken along lines AA'. As shown in Fig. 24A, the combination cutting and tissue collection removable probe 900 includes a proximal end 902 and a distal end 904. In the embodiment of Fig. 24A, the proximal end 902 may include cutting tool extending means 908 and tissue collection device extending means 906. The extending means 906, 908 may be configured as thumb dials or as any devices that are operative to extend the tissue collection device 918 and/or the cutting tool 914, such as a lever, for example. As shown in Fig. 24B, the wires and/or ribbons that constitute the cutting tool 914 and part of the tissue collection device 918 extend from the extending means 906, 908 along the length of the probe 900. The cutting tool 914 and the wire or ribbon of the tissue collection device 918 may be guided within the probe 900 by guides 912 and 910, respectively. Alternatively, the cutting tool 914 and the wire or ribbon of the tissue collection device 918 may be guided within the probe 900 by one or more internal lumens defined therein, in a manner similar as described relative to internal lumen 420 of tubular member 110, shown in Fig. 10. As the cutting tool 914 may be energized by RF energy, the cutting tool 914 may be separated from

the tissue collection device 918 by an air gap 920 (for example) of sufficient width to prevent arcing therebetween.

Fig. 25 is a top view of a removable cutting and tissue collection combination probe 925, according to another embodiment of the present invention. The embodiment of Fig. 25 differs from that shown in Fig. 24A in that the cutting tool 914 is separated from the tissue collection device 918 not by an air gap, but by an insulating material 922, such as a flexible plastic insulator. In the case wherein the cutting tool 914 includes an RF cutting device, the cutting tool 914 is electrically coupled to an RF power source, such as shown at 240. The configuration of the proximal end 902 of the probe shown in Fig. 25 also differs from that shown in Fig. 24A, in that a single extending means 926 is configured to activate both the cutting tool 914 and the tissue collection device 918, as the cutting tool 914 and the tissue collection device 918 are mechanically coupled to one another. The assembly including the mechanically coupled cutting tool 914 and tissue collection device 918 is coupled to the extending means 926 along the length of the probe, and is guided there along by an internal guide or lumen 924.

Fig. 26 is a side view of a removable cutting and tissue collection combination probe 950, according to a still further embodiment of the present invention, wherein the cutting tool 930 and the tissue collection device 932, 934 are shown in their extended (bowed) configurations. As shown, the probe 950 includes a proximal portion 902 and a distal portion 904. In the embodiment of Fig. 26, the proximal portion 902 includes a cutting tool extending means 926 that is configured to activate the cutting tool 930 and a tissue collection device extending means 944 that is configured to activate and extend the tissue collection device 932, 934. The tissue collection device 932, 934 may include a ribbon or wire 932 that

is adapted to bow (extend) out of and to retract back within a first window 942 defined within the probe 950. A thin and flexible sheet of material 934 is attached to the trailing edge of the wire or ribbon 932 to encapsulate or otherwise capture the cut tissue specimen upon activation of the tissue collection device 932, 934 and rotation of the tubular member 110 and probe 950, in the direction indicated by arrow 928, for example. Similarly, the cutting tool 930 (including an RF cutting tool, for example) is configured to extend out of and retract back into a second window 936. Both of the first and second windows 942, 936, when the probe 950 is inserted into the tubular member 110, are aligned with corresponding windows defined within the tubular member 110. One such window is shown in Fig. 10 at reference numeral 410.

The combination probe 950 of Fig. 26 may also include a plurality of through holes in fluid communication with an internal lumen 940 defined within the internal wall of the probe 950. In turn, the internal lumen 940 is in fluid communication with a port 942, which may be disposed at the proximal end of the probe 950. The through holes 938 may be utilized for the delivery of a fluid to the patient during the excisional procedure, such as antibiotic agents, analgesic agents or most any pharmaceutical agent. Such agents may be administered to the patient from the port 942. Alternatively, the port 942 may be coupled to suction and the through holes 938 may be utilized to suction out the excisional site of smoke, blood or other bodily fluids during or after the excisional procedure. Alternatively still, more than one port 942 may be provided in the proximal portion 902 and more than one lumen 940 may be defined along the length of the probe 950. The additional lumen may be in fluid communication with selected through holes 938. By this structure, both delivery of a pharmaceutical agent and suctioning may be provided within a single probe 950.

Although the probes shown in Figs. 18-26 have been described as removable probes adapted to fit at least partially within the excisional device 110, it should be noted that they need not be utilized therewith, and may be utilized independently thereof. For example, the cutting probe of Figs. 18-20 may be inserted and operated within soft tissue by themselves, without being inserted in the excisional device 110 of Fig. 10. Likewise, the tissue collection probe 800 may be utilized without the excisional device 110. For example, the cutting probe 700 of Figs. 18-20 may be utilized to cut the tissue specimen from the surrounding soft tissue, whereupon the tissue collection probe 800 of Figs. 21-23 may be inserted after removal of the cutting probe 700. Moreover, the features of each of the probes of Figs. 18-27C may be combined to best suit the application envisaged. The present invention, therefore, is not to be limited by the specific embodiments illustrated in Figs. 18-27C, as various other combinations of the disclosed features are possible, as those of skill will readily recognize.

Fig. 27A-27C are partial cross-sections of a tissue collection probe 1000, taken at the level of the tissue collection device 1018 thereof, as the probe 1000 captures and encapsulates a tissue specimen (lesion) 1008 within the patient's soft tissue, such as the breast. Turning first to Fig. 27A, the tissue collection device 1018 includes a thin sheet of flexible material 1002, which is folded on itself. One end of the thin flexible sheet of material 1002 is coupled at 1006 to the ribbon 1004, while the other end thereof is attached to the body of the probe 1000. The ribbon 1004 is configured to selectively extend out of and retract back into a window, such as shown at 806 in Fig. 23, for example. A tissue specimen (lesion) 1008 is to be excised from the soft tissue 1018. To do so, the excisional device 110 (and thus the probe 1000 fitted therein) is rotated in the direction of the arrow 1010, while the ribbon 1004 is

extended (bowed) in the direction of arrow 1012, shown in Fig. 27B. As the ribbon 1004 is extended, it unfolds and deploys the thin sheet of flexible material 1002, to at least partially encapsulate the tissue specimen 1008. As shown in Fig. 27C, the ribbon 1004 of the tissue collection device 1018 may then be retracted in the direction of arrow 1016 after the rotation 1014 (Fig. 27B) of the excisional device 110 causes the tissue specimen 1008 to be fully encompassed or encapsulated by the thin sheet of flexible material 1002. The excisional device 110 may then be removed from the patient, along with the collected tissue specimen 1008. To aid in the visualization of the tissue collection device 1018 during the excisional procedure, the ribbon 1004 thereof may include or be coated with a radiopaque material or may include a material readily visible by surface or intra-tissue ultrasound.

Fig. 28 is a flowchart of a soft tissue treatment method, according to another embodiment of the present invention. As shown in step S281, the cutting probe, such as shown at 700 in Figs. 18-20, is inserted into the excisional device 100. The excisional device 100 and cutting probe assembly 700 is then inserted into the patient's soft tissue, at the site of interest. The cutting tool 710 of the probe assembly 700 is extended (bowed) to cut the tissue specimen of interest from the surrounding tissue and the excisional device 100 is then rotated, as shown at step S282. Step S283 calls for the removal of the cutting probe 700 from the excisional device 100, leaving the excisional device 100 in place within the patient. A tissue collection probe, such as shown at 800 in Figs. 21-23, may then be inserted within the excisional device 100 (if not already inserted therein), as shown at S284. The tissue collection device 808-810 may be extended (bowed) out from the excisional device 100 and the assembly including the excisional device 100 and tissue collection probe 800 may then be rotated (in a direction opposite from the direction of rotation during the cutting step S282, for

example). As noted in step S285, this extends the collection device 808-810 along the same path as traveled by the cutting tool 710 of the cutting probe 700 in step S282 and causes the tissue collection device 808-810 to at least partially encompass (encapsulate) the tissue specimen, as shown, for example in Fig. 27C. The assembly including the excisional device 100 and tissue collection device 800 and the encapsulated tissue specimen may then be retracted from the patient, as shown at S286, and the specimen forwarded for histological analysis.

Alternatively, the combination cutting and tissue collection probe 900 may be inserted in the excisional device, instead of consecutively inserted the cutting probe 700 and tissue collection probe 800 therein. In this case, the tissue collection device 918 or 932, 934 may be activated simultaneously with or after the deployment of the cutting tool 914. Moreover, to better control the deployment of the cutting tool of Figs. 18-20 or 24A-26 and/or the tissue collection device of Figs. 21-23, 24A-26 or 27A-27C, an intra-tissue ultrasound sensor such as described relative to Figs. 1-17 may be used, to sweep a plane ahead of the cutting tool and/or tissue collection device as the tubular member 110 of the excisional device 100 rotates.

While the foregoing detailed description has described several embodiments of this invention, it is to be understood that the above description is illustrative only and not limiting of the disclosed invention. For example, the method of the present invention may also be carried out without the use of the tubular member 110, by inserting the probes disclosed herein relative to Figs. 18-27C directly in the patient's soft tissue, as the present cutting and tissue collection probes have utility independent of the excisional device 100. A number of other modifications will no doubt occur to persons of skill in this art. For example, the shape

and placement of the cutting device and tissue collection extending means (814, 906, 908, 926, 944) may differ from that illustrated and described herein, for ergonomical or other concerns. All such modifications, however, should be deemed to fall within the scope of the present invention. Thus, the invention is to be limited only by the claims as set forth below.

5

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193  
2194  
2195  
2196  
2197  
2198  
2199  
2200  
2201  
2202  
2203  
2204  
2205  
2206  
2207  
2208  
2209  
2210  
2211  
2212  
2213  
2214  
2215  
2216  
2217  
2218  
2219